



**ANSI/EIA-364-13D-2007**  
**Approved: July 2, 2007**

# **EIA STANDARD**

**TP-13D**

## **MATING AND UNMATING FORCE TEST PROCEDURE FOR ELECTRICAL CONNECTORS AND SOCKETS**

**EIA/ECA-364-13D**

(Revision of EIA-364-13C)

**JULY 2007**



**Electronic Components, Assemblies & Materials Association**

THE ELECTRONIC COMPONENTS SECTOR OF THE ELECTRONIC INDUSTRIES ALLIANCE



**EIA/ECA-364-13D**

## NOTICE

EIA Engineering Standards and Publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for his particular need. Existence of such Standards and Publications shall not in any respect preclude any member or nonmember of EIA from manufacturing or selling products not conforming to such Standards and Publications, nor shall the existence of such Standards and Publications preclude their voluntary use by those other than EIA members, whether the standard is to be used either domestically or internationally.

Standards and Publications are adopted by EIA in accordance with the American National Standards Institute (ANSI) patent policy. By such action, EIA does not assume any liability to any patent owner, nor does it assume any obligation whatever to parties adopting the Standard or Publication.

This EIA Standard is considered to have International Standardization implication, but the International Electrotechnical Commission activity has not progressed to the point where a valid comparison between the EIA Standard and the IEC document can be made.

This Standard does not purport to address all safety problems associated with its use or all applicable regulatory requirements. It is the responsibility of the user of this Standard to establish appropriate safety and health practices and to determine the applicability of regulatory limitations before its use.

(From Standards Proposal No. 5157 formulated under the cognizance of the CE-2.0 National Connector Standards Committee.

Published by

©ELECTRONIC INDUSTRIES ALLIANCE 2007  
Technology Strategy & Standards Department  
2500 Wilson Boulevard  
Arlington, VA 22201

***PRICE: Please refer to the current***  
**Catalog of EIA Electronic Industries Alliance Standards and Engineering**  
**Publications**  
**or call Global Engineering Documents, USA and Canada (1-800-854-7179)**  
**International (303-397-7956)**

All rights reserved  
Printed in U.S.A.

**PLEASE !  
DON'T VIOLATE  
THE  
LAW!**

This document is copyrighted by the EIA and may not be reproduced without permission.

Organizations may obtain permission to reproduce a limited number of copies through entering into a license agreement. For information, contact:

Global Engineering Documents  
15 Inverness Way East  
Englewood, CO 80112-5704 or call  
USA and Canada (1-800-854-7179), International (303-397-7956)

## CONTENTS

Clause		Page
1	Introduction .....	1
1.1	Scope .....	1
1.2	Test designation .....	1
2	Test resources .....	1
2.1	Equipment .....	1
2.2	Material .....	2
3	Test specimen .....	1
3.1	Method A .....	1
3.2	Method B .....	2
4	Test procedure .....	2
4.1	Method A .....	2
4.2	Method B .....	2
5	Details to be specified .....	3
6	Test documentation .....	3

(This page left blank)

## TEST PROCEDURE No. 13D

MATING AND UNMATING FORCE TEST PROCEDURE  
FOR  
ELECTRICAL CONNECTORS AND SOCKETS

(From EIA Standards Proposal No. 5157, formulated under the cognizance EIA CE-2.0 Committee on National Connector Standards, and previously published in EIA-364-13C.)

**1 Introduction**

## 1.1 Scope

This standard establishes a method to determine the forces required to mate and unmate electrical connectors or protective caps with connectors, connectors/sockets with gages or devices. Unless otherwise specified in the referencing document, method A shall be used.

## 1.2 Test designation

This test procedure contains 2 test methods as follows:

1.2.1 Method A is to determine the mating and unmating force of an electrical connector or socket to its intended mating connector or device.

1.2.2 Method B is to determine the mating and unmating force of an electrical connector or socket with a simulated mating device or gage.

**2 Test resources**

## 2.1 Equipment

The test equipment shall consist of:

2.1.1 Mounting fixtures that allow the specimens to be mounted in their normal manner.

2.1.2 Force or torque gages, of suitable range for the connector size under test, so that readings will be in the middle 50% of the scale, where practicable, with a nominal full scale accuracy of +2%.

2.1.3 Attachments and accessory type equipment as required to mate the test specimens and attach the force or torque gages (arbor press, etc.).

2.1.4 Simulated mating device or gage (applicable to method B only).

## 2.2 Material

2.2.1 Isopropyl alcohol, AR grade (applicable to method B only).

## 3 Test specimen

### 3.1 Method A

The specimen shall consist of a plug and a receptacle with all applicable contacts in place. All applicable hardware shall be assembled to the specimen including skirts, hoods, cable clamps, jackscrews, guide pins or sockets unless otherwise specified. The specimen shall not be lubricated or cleaned in any manner unless otherwise specified in the referencing document. If applicable the specimen shall be terminated as specified in the referencing document.

### 3.2 Method B

The specimen shall consist of the connector/socket and the gage(s) or device(s) as specified in the referencing document. Unless otherwise specified in the referencing document, all applicable contacts and hardware shall be installed including skirts, hoods, cable clamps, guide pins, etc. The specimen shall not be lubricated or cleaned and active latches are to be deactivated unless otherwise specified in the referencing document. If applicable, the specimen shall be terminated as specified in the referencing document.

## 4 Test procedure

### 4.1 Method A

This method is to determine the mating and unmating force of a connector to its intended mating connector or device. Unless otherwise specified, the specimen shall be mounted to mounting fixtures by the normal mounting means.

#### 4.1.1 Mating force

4.1.1.1 The two mating connectors shall be brought to a position where mechanical mating begins and the force or torque gage is at zero indication.

4.1.1.2 The connectors shall then be fully mated or coupled at a rate of 25.4 millimeters/minute, unless otherwise specified in the referencing document, and the peak force or torque required for mating shall be recorded.

#### 4.1.2 Unmating force

The mated connectors shall be fully unmated at a rate of 25.4 millimeters/minute, unless otherwise specified in the referencing document, and the peak force or torque required shall be recorded.

## 4.2 Method B

This method is to determine the mating and unmating forces of a connector with a simulated mating device or gage. The simulated device or gage shall be cleaned every five measurements with isopropyl alcohol, unless otherwise specified in the referencing document. The fixtures required to hold the specimen and the specimen shall be attached to the force measuring system then the system shall be zeroed.

### 4.2.1 Mating force

4.2.1.1 The two mating components shall be brought to a position just before mechanical mating begins and the force measuring system is indicating zero.

4.2.1.2 The gage/device shall then be fully mated to the connector/socket at a rate of 25.4 millimeters/minute, unless otherwise specified in the referencing document. The peak force required for mating prior to bottoming shall be recorded.

### 4.2.2 Unmating forces

The gage/device shall then be fully unmated from the connector/socket at a rate of 25.4 millimeters/minute unless otherwise specified in the referencing document. The peak force required for unmating shall be recorded.

## 5 Details to be specified

The following details shall be specified in the referencing document:

5.1 Number of specimens to be tested

5.2 Measurements to be made; mating force, unmating force, or both

5.3 Rates of mating and unmating, if other than specified in 4.1.1.2, 4.1.2, 4.2.1.2 and 4.2.2

5.4 Depth of mating if applicable

5.5 Lubrication or cleaning, if required

5.6 Wire type, gage, and length if applicable

5.7 Applicable hardware

5.8 Force or torque requirements

5.9 Test conditions, if other than standard atmospheric

5.10 Applicable to method B only: Details of the device(s) or gage(s) to be used for mating/unmating to the connector/socket, as well as the method and frequency of cleaning, if required



## **6 Test documentation**

Documentation shall contain the details specified in clause 5, with any exceptions, and the following:

6.1 Title of test

6.2 Specimen description including part number if applicable

6.3 If applicable, fixturing, gage details and gage part number

6.4 Test equipment used, and date of last and next calibration

6.5 Test procedure and method, if other than method A

6.6 Values and observation

6.7 Name of operator and start/finish date(s) of test

### EIA Document Improvement Proposal

If in the review or use of this document, a potential change is made evident for safety, health or technical reasons, please fill in the appropriate information below and mail or FAX to:

Electronic Industries Alliance  
Technology Strategy & Standards Department – Publications Office  
2500 Wilson Blvd.  
Arlington, VA 22201  
FAX: (703-875-8906)

Document No.:	Document Title:
Submitter's Name:	Telephone No.: FAX No.: e-mail:
Address:	
Urgency of Change: Immediate: <input type="checkbox"/> At next revision: <input type="checkbox"/>	
Problem Area: a. Clause Number and /or Drawing:  b. Recommended Changes:  c. Reason/Rationale for Recommendation:	
Additional Remarks:	
Signature:	Date:
<b><i>FOR EIA USE ONLY</i></b>  Responsible Committee:  Chairman:  Date comments forwarded to Committee Chairman:	

Revision History

Revision letter	Project number	Additions, changes and deletions
C	SP-5136	<p><b>Original test procedure is now method A.</b></p> <p><b>Added Method B and paragraph 2.1.4, 3.2, 4.2, 5.10 and 6.3.</b></p> <p><b>Revised paragraph 1.1, 4.1.1.2, 4.1.2, 5.2, 5.3, 6.2 and 6.5.</b></p>
D	5157	<p><b>Added paragraph 1.2, 2.2 and socket to title.</b></p> <p>Revised paragraph 2.1 4, 4.1 and 4.2.</p>







